



Compact Fans

DC Brushless Fans

Model	Bearing*	Voltage (VDC)	Current (mA)	Speed (RPM)	Air Flow (CFM)	Static Pressure (mm H ₂ O)	Noise (dBA)
60X60X20mm (Also available 60X60X25mm)							
6P12HSDC	Sleeve	12	180	4300	18	3.8	30
6P24HSDC	Sleeve	24	125	4300	18	3.8	30
80X80X25mm (Available upto 58 CFM)							
8P12HBDC	Ball	12	200	3000	38	4.5	34
8P24HBDC	Ball	24	150	3000	38	4.5	34
8P48HBDC	Ball	48	70	3000	38	4.5	34
92X92X25mm (Available upto 65 CFM)							
9P12HBDC	Ball	12	300	2500	55	5	40
9P24HBDC	Ball	24	200	2500	55	5	40
9P48HBDC	Ball	48	100	3000	55	5	40
120X120X38mm (Available upto 226 CFM)							
12P12HBDC	Ball	12	350	3000	105	8	50
12P24HBDC	Ball	24	250	3000	105	8	50
12P48HBDC	Ball	48	105	3000	105	8	50
172X150X51mm & 172X172X51mm (Available upto 310 CFM)							
17A12HBDC	Ball	12	1600	3000	210	13	60
17A24HBDC	Ball	24	750	3000	210	13	60
17A48HBDC	Ball	48	450	3000	210	13	60

Special Features - Fan Failure Alarm ■ Alarm Signal For Speed Monitoring ■ Higher Air Flow ■ Non-standard voltages

AC Axial Fans

Model	Bearing*	Voltage (VAC)	Frequency (Hz)	Current (mA)	Speed (RPM)	Watt (W)	Air Flow (CFM)	Static Pressure (mm H ₂ O)	Noise (dBA)
80X80X25mm									
8A230HBAC	Ball	230	50/60	70/60	2300/2800	14/12	21/25	4/4.8	29/34
92X92X25mm									
9A230HBAC	Ball	230	50/60	70/60	2300/2800	14/12	36/42	5/6	36/38
120X120X38mm									
12A230HBAC	Ball	230	50/60	100/90	2600/2800	18/17	95/102	8.4/9.4	42/45
172X150X51mm & 172X172X51mm (Available upto 250/293 CFM)									
17A230HBAC	Ball	230	50/60	250/245	2600/2750	38/37	190/235	16/21	45/50
220ΦX60mm & 220X220X60mm									
22A230HBAC	Ball	230	50	320	2300	50	360	23	56

Also available 24VAC, 115VAC & 415VAC
 Ask for Low Noise versions

*All fan models are available in sleeve bearing also

Specifications subject to change without notice